




• VC-S Series



The VC-S1 series is surface mount voltage controlled crystal oscillator designed primarily for use in phase locked loops, phase shift keying and other telecommunication applications such as ADSL, Cable modem etc. VC-S1 is 5V power supply and VC-S3 is 3.3V power supply.

FEATURES





- Miniature Package
- Industry Standard
- TTL/HCMOS output compatible
- Tri-State Enable/Disable
- Tape and Teel
- 3.3V available

Electrical Specifications

Parameter	Condition	VC-S1	VC-S3
Frequency Range*	F ₀	1.750MHz~45.000MHz	1.750MHz~45.000MHz
Frequency Calibration	At 25°C	± 15ppm	
Temperature Stability	Over T _{OPR}	± 15ppm, ± 25ppm, ± 50ppm	
Stability vs. power change	V _{DD} +/-5%	± 5ppm	
Stability vs. load change	15pF+/-10%	± 3ppm	
Pullability	Over Control Voltage Range	± 50ppm, ± 100ppm, ± 200ppm	± 50ppm, ± 100ppm, ± 150ppm
Control Voltage Range		0.5~4.5V	0~3.3V
Operating Temperature Range	T _{OPR}	0°C~70°C (-40°C~+85°C option)	
Storage Temperature Range	T _{STG}	-55°C~+125°C	
Power Supply Voltage	V _{DD}	5.0V+/-5%	3.3V+/-5%
Aging (First Year)	25°C ± 3°C	± 5ppm	
Supply Current	I _{DD}	30mA Max	
Output Symmetry	Sym	40/60%(45/55% Option)	
Rise time	T _r	10 nS Max	8 nS Max
Fall Time	T _f	10 nS Max	8 nS Max
Output Voltage	V _{OH}	90% V _{DD} min	
	V _{OL}	10% V _{DD} max	
Output Load		15pF max	
Start-up Time	T _s	10mS Max	


* Frequency over 40.000Mhz, please consult factory.

Mechanical Dimensions(mm)




Pin	Connection
#1	V _{control}
#2	E/D
#3	GND
#4	Output
#5	N.C.
#6	V _{DD}

Test Circuit



**Includes stray and probe capacitance

Output Waveform



***note: A 0.01µF bypass capacitor should be placed between V_{DD}(Pin6) and GND(Pin3) to Minimize power supply line noise

TAIWAN:

HOSONIC ELECTRONIC CO., LTD.
23-1 LANE 84. CHUN YING ST. SHULIN CHEN.
TAIPEI 23804. TAIWAN. R.O.C.

☎: 886-2-86875200
☎: 886-2-26816456

CHINA:

HANGZHOU HOSONIC ELECTRONIC CO., LTD.
XUNSHAN LIANGZHU TOWN MOGANSHAN ROAD
HANGZHOU, ZHEJIANG, CHINA

☎: (86)-571-88778189
☎: (86)-571-88778857